

HSC

**Howard Supply Company, Inc.**



**TECHNICAL BULLETIN  
#6622 STEEL SPRAY WASH**

THIS PRODUCT IS A HEAVY-DUTY, ALKALINE COMPOUND DESIGNED SPECIFICALLY FOR USE AS A SPRAY CLEANER. IT IS OFF-WHITE IN COLOR, GRANULAR, DUST-FREE, AND IS EASILY DISSOLVED IN WARM WATER. #6622 IS FOR USE PRIMARILY ON FERROUS METALS AND IS LOW-FOAMING WITH EXCELLENT DETERGENCY PROPERTIES. IT WILL NOT SPOT, STREAK, OR STAIN, AND CONTAINS GOOD WETTING AND SOIL SUSPENSION INGREDIENTS. NORMAL PRECAUTIONARY METHODS, AS USED IN HANDLING HIGHLY ALKALINE MATERIALS, SHOULD BE FOLLOWED.

**PROCEDURE:**

*CONCENTRATION.....TWO TO EIGHT OUNCES PER GALLON*

*TEMPERATURE.....90-180 DEGREES F.*

*TIME.....FIFTEEN SECONDS TO THREE MINUTES*

*PRESSURE.....20-60 P.S.I.*

AFTER USING #6622 ON PARTS, IT IS ACCEPTABLE TO FOLLOW WITH AN ELECTRO CLEANER OR HOT RINSE FOR FURTHER PROCESSING.

TEST PROCEDURE IS CARRIED OUT WITH EITHER TEST KITS OR LABORATORY TITRATION METHODS. FACTORS SUPPLIED UPON REQUEST.